# **SAFETY DATA SHEET**

#### CRAFCO PTC COMP-B

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : CRAFCO PTC COMP-B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product use: Two component coating for interior use.

1.3. Details of the supplier of the safety data sheet

Akzo Nobel Decorative Coatings,

Wexham Road, Slough, Berkshire,

United Kingdom, SL2 5DS, Tel.: +44 (0) 333 222 70 70 www.sikkens.co.uk

e-mail address of person : sikke

: sikkens.advice@akzonobel.com

responsible for this SDS

1.4 Emergency telephone number

**Telephone number :** Emergency number is - 01753 550000 (24 hours) International

Sikkens 24 hours emergency number: Tel.: +31 71

3086944

Version : 7

Date of previous issue : 15-7-2014.

# **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

**Product definition:** Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Kin Irrit. 2, H315
Eye Irrit. 2, H319
Skin Sens. 1, H317
Aquatic Chronic 2, H411

Ingredients of unknown : 0%

toxicity

Ingredients of unknown : 0%

ecotoxicity

Classification according to Directive 1999/45/EC [DPD]

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Date of issue/Date of revision: 20-9-2014. Page: 1/12

# **SECTION 2: Hazards identification**

Classification : Xi; R36/38

R43 N; R51/53

**Human health hazards**: Irritating to eyes and skin. May cause sensitisation by skin contact.

Environmental hazards : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

See Section 16 for the full text of the R phrases or H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2. Label elements

Hazard pictograms





Signal word : Warning

**Hazard statements**: H319 - Causes serious eye irritation.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H411 - Toxic to aquatic life with long lasting effects.

**Precautionary statements** 

General: P102 - Keep out of reach of children.

P101 - If medical advice is needed, have product container or label at hand.

Prevention : P280 - Wear protective gloves.

P262 - Do not get in eyes, on skin, or on clothing. P264 - Wash hands thoroughly after handling.

Response : P312 - Call a POISON CENTER or physician if you feel unwell.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional,

national or international regulations.

Hazardous ingredients : reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average

molecular weight ≤ 700)

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Supplemental label

elements

: Contains epoxy constituents. May produce an allergic reaction.

Annex XVII - Restrictions : Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and

articles

**Special packaging requirements** 

Containers to be fitted : Not applicable.

with child-resistant

fastenings

Tactile warning of danger: Not applicable.

#### 2.3. Other hazards

Other hazards which do : None known.

not result in classification

The mixture may be a skin sensitiser. It may also be a skin irritant and repeated contact may increase this effect.

Date of issue/Date of revision: 20-9-2014. Page: 2/12

## SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures : Mixture

			Classification		
Product/ingredient name	Identifiers	% (w/w)	67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	Туре
Eaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	EC: 500-033-5 CAS: 25068-38-6 Index: 603-074-00-8	>=90	Xi; R36/38 R43 N; R51/53	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	[1]
oxirane, mono[ (C12-14-alkyloxy)	EC: 271-846-8	>=5 - <10	Xi; R38	Skin Irrit. 2, H315	[1]
methyl] derivs.	CAS: 68609-97-2 Index: 603-103-00-4		R43	Skin Sens. 1, H317	
			See Section 16 for the full text of the R- phrases declared above.	See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### **Type**

Inhalation

Skin contact

**Protection of first-aiders** 

Ingestion

- Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

#### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

**General :** In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.

Eye contact : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical

: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2. Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the EC 1272/2008 regulation and classified for toxicological hazards accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption

Date of issue/Date of revision: 20-9-2014.

#### SECTION 4: First aid measures

through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Based on the properties of the epoxy constituent(s) and considering toxicological data on similar mixtures, this mixture may be a skin sensitiser and an irritant. It contains low molecular weight epoxy constituents which are irritating to eyes, mucous membrane and skin. Repeated skin contact may lead to irritation and to sensitisation, possibly with cross-sensitisation to other epoxies. Skin contact with the mixture and exposure to spray mist and vapour should be avoided.

Contains reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq$  700), oxirane, mono[(C12-14-alkyloxy)methyl] derivs.. May produce an allergic reaction.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Notes to physician: Treat symptomatically. Contact poison treatment specialist immediately if large quantities

have been ingested or inhaled.

**Specific treatments**: No specific treatment.

See toxicological information (Section 11)

# **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media

: Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.

Unsuitable extinguishing media

: Do not use water jet.

#### 5.2. Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

#### 5.3. Advice for firefighters

Special protective actions for fire-fighters

: Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

Special protective equipment for fire-fighters

: Appropriate breathing apparatus may be required.

#### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.

For emergency responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

# 6.2. Environmental precautions

: Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

# 6.3. Methods and material for containment and cleaning up

: Intain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

Date of issue/Date of revision : 20-9-2014. Page: 4/12

# **SECTION 6: Accidental release measures**

# 6.4. Reference to other sections

: See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

# **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

# 7.1 Precautions for safe handling

: Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits.

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.

Operators should wear antistatic footwear and clothing and floors should be of the conducting type.

Keep away from heat, sparks and flame. No sparking tools should be used.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see Section 8).

Never use pressure to empty. Container is not a pressure vessel.

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

Do not allow to enter drains or watercourses.

#### Information on fire and explosion protection

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

# 7.2 Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations.

#### Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

#### Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

#### Seveso II Directive - Reporting thresholds (in tonnes)

#### **Danger criteria**

Category	Notification and MAPP threshold	Safety report threshold
2: Hazardous to the aquatic environment - Chronic 2 C9ii: Toxic for the environment	200 200	500 500

#### 7.3 Specific end use(s)

solutions

Recommendations : Not available.

Industrial sector specific : Not available.

# SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker or exposure or environmental releases.

#### 8.1 Control parameters

#### Occupational exposure limits

No exposure limit value known.

Date of issue/Date of revision: 20-9-2014. Page: 5/12

## SECTION 8: Exposure controls/personal protection

procedures

Recommended monitoring: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres -General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

No DNELs/DMELs available.

#### **PNECs**

No PNECs available

#### 8.2 Exposure controls

controls

Appropriate engineering : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

#### **Individual protection measures**

Hygiene measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating,

smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety

showers are close to the workstation location.

**Eye/face protection** 

: Use safety eyewear designed to protect against splash of liquids.

Skin protection

**Body protection** : Personnel should wear antistatic clothing made of natural fibres or of high-

temperature-resistant synthetic fibres.

Other skin protection : Appropriate footwear and any additional skin protection measures should be

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Respiratory protection: If workers are exposed to concentrations above the exposure limit, they must use

appropriate, certified respirators.

**Environmental exposure**: Do not allow to enter drains or watercourses.

controls

# SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

#### **Appearance**

**Physical state** : Liquid.

Colour : Not available. **Odour** : Not available. **Odour threshold** : Not available. pН : Not available. Melting point/freezing point : Not available. Initial boiling point and boiling : Not applicable.

range

Flash point : Closed cup: 100°C **Evaporation rate** : Not available. Upper/lower flammability or : Not available.

explosive limits

Date of issue/Date of revision: 20-9-2014. Page: 6/12

# **SECTION 9: Physical and chemical properties**

Vapour pressure : Not available.
Vapour density : Not available.

Relative density : 1,133

**Solubility(ies)** : Easily soluble in the following materials: cold water.

Solubility in water : Not available.

Partition coefficient: n-octanol/ : Not available.

water

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity: Kinematic (room temperature): 44,13 cm<sup>2</sup>/s

Explosive properties : Not available.

Oxidising properties : Not available.

9.2. Other information
No additional information.

# SECTION 10: Stability and reactivity

**10.1. Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2. Chemical stability** : Stable under recommended storage and handling conditions (see Section 7).

10.3. Possibility of : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4. Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products.

10.5. Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

10.6. Hazardousdecomposition productsUnder normal conditions of storage and use, hazardous decomposition products should not be produced.

# SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

There are no data available on the mixture itself. The mixture has been assessed following the EC 1272/2008 regulation and classified for toxicological hazards accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Based on the properties of the epoxy constituent(s) and considering toxicological data on similar mixtures, this mixture may be a skin sensitiser and an irritant. It contains low molecular weight epoxy constituents which are irritating to eyes, mucous membrane and skin. Repeated skin contact may lead to irritation and to sensitisation, possibly with cross-sensitisation to other epoxies. Skin contact with the mixture and exposure to spray mist and vapour should be avoided.

Contains reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700), oxirane, mono[(C12-14-alkyloxy)methyl] derivs.. May produce an allergic reaction.

Date of issue/Date of revision: 20-9-2014. Page: 7/12

# **SECTION 11: Toxicological information**

**Acute toxicity** 

**Conclusion/Summary** 

: Not available.

**Acute toxicity estimates** 

Not available.

#### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
reaction product: bisphenol- A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	Eyes - Mild irritant	Rabbit	-	-	-
	Eyes - Moderate irritant	Rabbit	-	-	-
	Eyes - Severe irritant	Rabbit	-	-	-
	Skin - Moderate irritant	Rabbit	-	-	-
	Skin - Severe irritant	Rabbit	-	-	-
oxirane, mono[ (C12-14-alkyloxy)methyl] derivs.	Skin - Moderate irritant	Rabbit	-	-	-

Conclusion/Summary

: Not available.

**Sensitisation** 

Conclusion/Summary

: Not available.

**Mutagenicity** 

**Conclusion/Summary** 

: Not available.

Carcinogenicity

Conclusion/Summary

: Not available.

**Reproductive toxicity** 

**Conclusion/Summary** 

: Not available.

**Teratogenicity** 

**Conclusion/Summary** 

: Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

Other information : Not available.

# SECTION 12: Ecological information

#### 12.1. Toxicity

There are no data available on the mixture itself.

Do not allow to enter drains or watercourses.

The mixture has been assessed following the EC 1272/2008 regulation and is classified for ecotoxicological properties accordingly. See sections 2 and 3 for details.

Page: 8/12

**Conclusion/Summary**: Not available.

#### 12.2. Persistence and degradability

**Conclusion/Summary**: Not available.

12.3. Bioaccumulative potential

12.4. Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Date of issue/Date of revision : 20-9-2014.

## SECTION 12: Ecological information

Mobility : Not available.

12.5. Results of PBT and vPvB assessment

PBT : Not applicable.

P: Not available. B: Not available. T: Not available.

vPvB : Not applicable.

vP: Not available. vB: Not available.

12.6. Other adverse effects: No known significant effects or critical hazards.

## **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

#### **Product**

Methods of disposal: The generation of waste should be avoided or minimised wherever possible. Disposal of this

product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities

with jurisdiction.

**Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.

**Disposal considerations**: Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

For further information, contact your local waste authority.

**Packaging** 

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste

packaging should be recycled. Incineration or landfill should only be considered

when recycling is not feasible.

Disposal considerations : Using information provided in this safety data sheet, advice should be obtained from

the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Dispose of containers contaminated by the product in accordance with local or

national legal provisions.

**Special precautions**: This material and its container must be disposed of in a safe way. Care should be

taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14: Transport information**

	ADR	IMDG
14.1. UN number	UN3082	UN3082
14.2. UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin)
14.3. Transport hazard class(es) Class	9	9
Subsidiary class	-	-
14.4. Packing group	III	III

Date of issue/Date of revision: 20-9-2014. Page: 9/12

CRAFCO PTC COMP-B				
SECTION 14: Transport information				
14.5. Environmental hazards				
Marine pollutant	Yes.	Yes.		
Marine pollutant substances		reaction product: bisphenol-A-(epichlorhydrin); epoxy resin		
14.6. Special precautions for user  Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.				
HI/Kemler number	90			
Emergency schedules (EmS)		F-A, S-F		
14.7 Transport in bul according to Annex I MARPOL 73/78 and t Code	ll of			
Additional information	The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.		
	<u>Tunnel code</u> (E)			

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorisation

**Annex XIV** 

None of the components are listed.

**Substances of very high concern** 

None of the components are listed.

Annex XVII - Restrictions : Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

**VOC** : Not available.

**Europe inventory** : At least one component is not listed.

**Seveso II Directive** 

This product is controlled under the Seveso II Directive.

**Danger criteria** 

Category

: Hazardous to the aquatic environment - Chronic 2

C9ii: Toxic for the environment

**International regulations** 

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Date of issue/Date of revision: 20-9-2014. Page: 10/12

## **SECTION 15: Regulatory information**

Not listed.

**Stockholm Convention on Persistent Organic Pollutants** 

Not listed.

**Rotterdam Convention on Prior Inform Consent (PIC)** 

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

15.2 Chemical Safety

: Not applicable.

**Assessment** 

#### **SECTION 16: Other information**

CEPE code

: 1

Indicates information that has changed from previously issued version.

Abbreviations and acronyms: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN

= REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classific	ation	Justification	
Kin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411		Calculation method Calculation method Calculation method Calculation method Calculation method	
Full text of abbreviated H statements	: H315 H317 H319 H411	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.	
Full text of classifications [CLP/GHS]	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317	LONG-TERM AQUATIC HAZARD - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITIZATION - Category 1	

Full text of abbreviated R

phrases

: R38- Irritating to skin.

R36/38- Irritating to eyes and skin.

R43- May cause sensitisation by skin contact.

R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Full text of classifications

[DSD/DPD]

: Xi - Irritant

N - Dangerous for the environment

Date of printing

Date of issue/ Date of

: 24-9-2014. : 20-9-2014.

revision

Date of previous issue

: 15-7-2014.

: 7

Version

Notice to reader

Date of issue/Date of revision: 20-9-2014. Page: 11/12

### **SECTION 16: Other information**

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to AkzoNobel.

Head Office

Akzo Nobel Decorative Coatings B.V, Rijksstraatweg 31, 2171 AJ Sassenheim, the Netherlands

Date of issue/Date of revision: 20-9-2014. Page: 12/12